

**5T HVAC  
w/10kw Heat Strip  
on AT Cart**  
Part # 9747



#### Includes:

- 2 Integrated 30' power supply cords (heat pump and heat strip)
- Remote or Panel-mounted thermostat control
- Integrated 600-LBS capacity top-mount gear rack,
- Solid rubber all-terrain tires
- Swivel axle with integrated T-Handle
- Heavy duty PVC ducts 12"dia/14"dia x 10' L
- Hinged side-mount lift handles

### KEY FEATURES

**FAST:** With its top-mount gear rack; wide, large diameter, high-density foam-filled wheels; and integrated push/lift handles; ZUMRO's 5T Portable HVAC Unit is designed to facilitate quick deployments

**SIMPLE:** ZUMRO's 5T Portable HVAC Unit features a side-by-side plenum configuration with uniform inlet/outlet ports, "plug and play" power cords, and remote thermostatic control, making the system extremely easy to connect and place into operation

**INTEGRATED:** Single, integrated unit offers 62,000 BTU/HR cooling, 60,000 BTU/HR heating (expandable) and dehumidification in one compact package

**DURABLE:** Our rugged 14-gauge, powder-coated steel frame combined with shock-absorbing materials and all-weather capability ensure this HVAC will perform in the harshest conditions

**CAREFREE:** ZUMRO's 25' remote "fast acting" thermostatic control features an intuitive user interface and is designed specifically to alleviate temperature swings, ensuring that even an untrained person can properly deploy and operate the 5T Portable HVAC Unit

**VERSATILE:** ZUMRO provides a 400-LBS capacity gear rack as standard on our 5T Portable HVAC

#### CONSTRUCTION:

Frame: 1"x2" and 1"x2" Powder-Coated 14-Gauge Steel  
Casters: Solid Rubber All-Terrain Tires  
Handles: Integrated, Ergonomic Push/Lift Handles (x4)  
Gear Rack: 600-LBS Capacity, Integrated Top-Mount Ducts:  
12"/14"x10' HD PVC with Integrated Belt Buckle Closure  
Thermostat: Optional remote Unit with 25' Cord and Carrying Case

#### PERFORMANCE:

Cooling Capacity: 62,000 BTU/HR  
Heating Capacity (Heat Pump Only): 60,000 BTU/HR  
Resistance Heater Capacity (Optional): +34,000 BTU/HR  
Air Supply: 2,250 CFM @ 0.1 Wet Coil  
Dehumidifying: 50% RH Max  
Operating Temperature Range: -40 DEG F - 125 DEG F  
F Rating Ambient: 95 DEG F  
Max Power Draw (Heat Pump): 8.2kW @ 34.1A  
Max Power Draw (Resistance Heater): +10kW @ 43A

#### DIMENSIONS:

Unit Dimensions (LxWxH): 61" x 35.5" x 53.5"  
Unit Weight: 650 lbs

