

### 5T HVAC on A/T Cart



#### Part # 9731 includes:

- Integrated 30' power supply cord (heat pump only),
- Remote thermostat with 25' cord and storage case,
- Integrated 400-LBS capacity top-mount gear rack,
- High-density foam-filled wheels, 8"x2.5" (x2 fixed, x2 swivel),
- Heavy duty PVC ducts 12"dia x 10' L (x2)

#### KEY FEATURES

**FAST:** With its top-mount gear rack; wide, large diameter, high-density foam-filled wheels; and integrated push/lift handles; ZUMRO's 5T Portable HVAC Unit is designed to facilitate quick deployments

**SIMPLE:** ZUMRO's 5T Portable HVAC Unit features a side-by-side plenum configuration with uniform inlet/outlet ports, "plug and play" power cords, and remote thermostatic control, making the system extremely easy to connect and place into operation

**INTEGRATED:** Single, integrated unit offers 62,000 BTU/HR cooling, 60,000 BTU/HR heating (expandable) and dehumidification in one compact package

**DURABLE:** Our rugged 14-gauge, powder-coated steel frame combined with shock-absorbing materials and all-weather capability ensure this HVAC will perform in the harshest conditions

**CAREFREE:** ZUMRO's 25' remote "fast acting" thermostatic control features an intuitive user interface and is designed specifically to alleviate temperature swings, ensuring that even an untrained person can properly deploy and operate the 5T Portable HVAC Unit

**VERSATILE:** ZUMRO provides a 400-LBS capacity gear rack as standard on our 5T Portable HVAC, making it the

#### CONSTRUCTION:

Frame: 1"x2" and 1"x2" Powder-Coated 14-Gauge Steel  
Casters: 8"x2.5" Turf Tires Filled with High-Density Foam  
Handles: Integrated, Ergonomic Push/Lift Handles (x2)  
Gear Rack: 400-LBS Capacity, Integrated Top-Mount  
Ducts: 12"x10' HD PVC with Integrated Belt Buckle Closure  
Thermostat: Remote Unit with 25' Cord and Carrying Case  
Power Cord:  
(Heat Pump): 30' UL-Rated 50A CS6365

#### PERFORMANCE:

Cooling Capacity: 62,000 BTU/HR  
Heating Capacity (Heat Pump Only): 60,000 BTU/HR  
Air Supply: 2,250 CFM @ 0.1 Wet Coil  
Dehumidifying: 50% RH Max  
Operating Temperature Range: -40 DEG F - 125 DEG F  
Rating Ambient: 95 DEG F  
Max Power Draw (Heat Pump): 8.2kW @ 34.1A

#### DIMENSIONS:

Unit Dimensions (LxWxH): 61" x 35.5" x 47.5"  
Unit Weight: 580 LBS



800.932.6003  
**ZUMRO.COM**

