

Compact, Upright Design Fits Easily Into Tight Spaces

HEPA-AIRE PAS1200 Portable Air Scrubber features variable airflow control from 150 cfm to 900 cfm. The PAS1200 is capable of maintaining 6 ACH in spaces up to 7,500-9,000 ft³ at peak rated airflow. The PAS1200 Portable Air Scrubber is designed to employ up to four filter stages to remove potentially hazardous airborne particles from water-loss restoration projects.

- Airflow* 150-900 cfm
- Air Changes Per Hour 6 ACH @ 9,000 ft³
- Net Weight with Filters 85 pounds
- Dimensions 19.25" L x 22" W x 39" H
- Power Supply Requirements 120 VAC, 60Hz, 15 amps
- Motor/Blower High-efficiency airfoil type motorized impeller rated for 100,000 hours, with thermal overload protection & auto reset
- Electrical Safety NRTL-certified to comply with UL Std. 507 & CAN/CSA Std. #C22.2 No. 113-M1984
- Cabinet Material and Construction
- 20 gauge corrosion-resistant stainless steel with
- Solid, aircraft-type rivets
- No Tools Pre-Filter Access Hinged door secured by rotating latches, with full perimeter gasket seal to protect against bypass of contaminated air
- Pre-filter Mounting Individual shelves for each pre-filter

SPECIFICATIONS

- Stage 1 pre-filter - 1" deep FIBER-TRAPPER® pre-filter for capturing large particulates
- Stage 2 pre-filter - 2"-deep pleated prefilter
- Stage 3 pre-filter - 2"-deep high-capacity VAPOR-LOCK carbon filter for gas and odor adsorption.
- Final stage - HEPA filter - IEST compliant metal-frame, HEPA filter with tested /certified minimum efficiency of 99.97% @ 0.3 microns

*Airflow ratings are based on third party testing conducted @ 120 VAC with clean filters in accordance with generally accepted testing methods using highly accurate electronic flow measurement equipment. Different testing methods may produce higher or lower results. Ratings have been rounded off to the nearest 50 cfm for convenience.

